

# UM-16 RELS/KSR-G24/1/NPE/E/PLC

Order No.: 2962036



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2962036>

VARIOFACE output expansion module, with plug-in bases for 16 miniature relays, 1 PDT each, for 24 V DC (without relays), with additional N and PE connection terminal blocks



## Commercial data

GTIN (EAN)	 4 017918 087098
Note	Made-to-order
sales group	I640
Pack	1 pcs.
Customs tariff	85364190
Catalog page information	Page 255 (IF-2009)

## Product notes

WEEE/RoHS-compliant since:  
09/14/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Input data

Nominal input voltage $U_N$	24 V DC (Related to the assembly)
Type of protection	Free-wheeling diode
Protective circuit/component	Damping diode
Operating voltage display	Green LED

Status display/channel	Yellow LED
------------------------	------------

**Output data**

Contact type	1 N/O contact
Maximum switching voltage	250 V AC/DC
Limiting continuous current	4 A
Max. total current (N)	14 A

**General data**

No. of channels	16
Compatible components	Miniature relay, REL-MR- 24DC/21HC
With components	No
Width	267 mm
Height	111.5 mm
Depth	59 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Test voltage	2.5 kV (50 Hz, 1 min.)
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Mounting position	Any
Assembly instructions	In rows with zero spacing
Pollution degree	2
Surge voltage category	III
Housing insulation material	PVC, side panel PA non-reinforced,
Color	green

**Connection data**

Connection 1	Coil side
Type of connection	Flat-ribbon cable plug connector in acc. with IEC 60603-13
Number of positions	20
Connection 2	Contact side
Type of connection	Screw connection
Number of positions	6
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>

Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Screw thread	M3
Stripping length	8 mm

**Certificates / Approvals**



Certification


GOST

**Additional products**

Item	Designation	Description
2962023	UM-16 RELS/KSR-G24/ 1/N/PE/ PLC	VARIOFACE output module, with plug-in bases for 16 miniature relays, 1 PDT each, for 24 V DC (without relays), with additional N and PE connection terminal blocks

**Diagrams/Drawings**

Circuit diagram



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;